



Notes:

- Rated voltage/current: UL1059 600V/15A
IEC 800V/24A
- Operation temperatures: -40°C ~ +105°C
- Withstanding Voltage: AC3500V/1min
- Insulation Resistance: 1000MΩ /DC500V
- Wire Range: 28~12AWG, 2.5mm²
- Unidimensional Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to	over	over	to	over	over	over	over	
6	6 to 10	10 to 24	30 to 30	30 to 60	60 to 100	100 to 150	150	∅
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1	0.05/10

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE

WS2.5-END-CO-Housing 61A0Y01A(H) 1		PA66	UL94V-
ITEM	NAME OF PART	NO. OF PART	Q'TY MATERIAL NOTES
STANDARD LIST	MM (INCH)	DEPTO LYK	DATE 10/21/07
	TOLERANCES EXCEPT AS NOTED	CHKD	DATE
	MM	MFO	DATE
	.0 ±	APPVL	DATE
	.000 ±	MATERIAL :	
ANGLES ± 1°	G. B :		
THIRD ANGLE PROJECTION	FINISH :		
	SCALE : 1:1		

NAME		WS2.5-END-CO-01P-1Y-00A(H)	
DRAWING NO.	WS2.5-END-CO-E01	SIZE	A3
/PART NO.		REV TO	06/28/08
DO NOT SCALE DRAWING		SHEET	1 OF 1

3	DG242-Shrapnel	X000000990(H)2	Stainless steel
2	WS2.5-MID-CO-Current Connector	6160B00010(H)1	Copper Tin Plated