



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		图面整理	CSX	12/23/05
△		增加UL刻字	CSX	06/05/06
△		修改脚宽	CSX	09/21/06
△		工程变更:品名商标更改到侧面	WLM	07/19/08

- NOTES:
- Pitch: 8.25mm , Poles: 2P-26P
 - Rated voltage/current: UL 300V/20A
IEC 450V/32A
 - Operation temperatures: -40° C ~ +105° C
 - Withstanding Voltage: AC2000V/1Min
 - Insulation Resistance: 500MΩ/DC500V
 - Wire Range: 22-12AWG, 4.0mm²
 - Max. Torque Value: M3, 5.10Kgf.cm
 - Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm				
to	over	over	over	over	over	
6	10	10	30	60	100	150
to	to	to	to	to	to	to
6	10	24	30	60	100	150
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7
						±1.0
						0.05/10

3	3*6(6*6) bright-Screw	S000000450(H)	XX	Steel	Ni Plated
2	DG25C-Pin Header	5001B00010(H)	XX	Brass	SnCe
1	DG35C-B-Housing	5002A0YXXA(H)	1	PA66	UL94V-0

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES												
<table border="1"> <tr> <td>← MM (INCH) →</td> <td>DFTO DZJ</td> <td>DATE 10/25/05*</td> </tr> <tr> <td>TOLERANCES EXCEPT AS NOTED</td> <td>CHKD</td> <td>DATE</td> </tr> <tr> <td></td> <td>MFO</td> <td>DATE</td> </tr> <tr> <td></td> <td>APPVL</td> <td>DATE</td> </tr> </table>		← MM (INCH) →	DFTO DZJ	DATE 10/25/05*	TOLERANCES EXCEPT AS NOTED	CHKD	DATE		MFO	DATE		APPVL	DATE	宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD			
← MM (INCH) →	DFTO DZJ	DATE 10/25/05*															
TOLERANCES EXCEPT AS NOTED	CHKD	DATE															
	MFO	DATE															
	APPVL	DATE															
DETACHED LISTS		NAME DG35C-B-XXP-1Y-00A(H)															
<table border="1"> <tr> <td>MM</td> <td>±</td> </tr> <tr> <td>.0</td> <td>±</td> </tr> <tr> <td>.00</td> <td>±</td> </tr> <tr> <td>.000</td> <td>±</td> </tr> </table>		MM	±	.0	±	.00	±	.000	±	MATERIAL :		DRAWING NO. DG35C-E07					
MM	±																
.0	±																
.00	±																
.000	±																
ANGLES ± 1°		G.E :		SIZE A3													
		FINISH :		REV T4													
THIRD ANGLE PROJECTION		SCALE : 1:1		07/19/08*													
DO NOT SCALE DRAWING			SHEET 1 OF 1														